

Claim Amendments

1.(currently amended) A system for modular construction comprising:

(A) a plurality of structural members, each of said plurality of structural members comprising:

- (1) a first lengthwise side and a second lengthwise side opposite said first lengthwise side, each of said lengthwise sides being generally parallel to each other;
- (2) a first widthwise side and a second widthwise side opposite said first widthwise side, each of said widthwise sides being generally parallel to each other;
- (3) at least two slots along one of said lengthwise sides, each of said slots comprising:
 - (a) a pair of generally parallel slot sides;
 - (b) an open end along one of said lengthwise sides;
 - (c) a slot axis parallel to and disposed equally between said slot sides;

wherein a first one of said at least two slots defines a first outside slot which is located nearest to the first widthwise side and a second one of said at least two slots defines a second outside slot which is located nearest to the second widthwise side; and

wherein the distance between the slot axis of the first outside slot and the first widthwise side is a predetermined slot-to-side distance and the distance between the slot axis of the second outside slot and the second widthwise side is a whole-number multiple of the predetermined slot-to-side distance; and

wherein the distance between each of the slot axes of the at least two slots along one of said lengthwise sides is a whole-number multiple of the predetermined slot-to-side distance; and

wherein ~~each of said plurality of structural members is adapted to be detachably connected slot-to-slot to each of the other of said plurality of structural members~~ each of said at least two slots along one of said lengthwise sides of one of said plurality of structural members is detachably and selectively connected slot-to-slot to one of all of said at least two slots along one of said lengthwise sides of each of the other of said plurality of structural members.

- 2.(original) The system for modular construction of Claim 1 wherein each of said slots has a substantially equal slot depth.
- 3.(original) The system for modular construction of Claim 1 wherein the distance between the slot axis of the second outside slot and the second widthwise side is equal to the predetermined slot-to-side distance.
- 4.(currently amended) The system for modular construction of Claim 1 wherein at least one of said structural members includes a slot along the lengthwise side opposite the lengthwise side having said at least two slots.
- 5.(original) The system for modular construction of Claim 1 wherein at least one of said structural members includes a slot along the first widthwise side.

6.(original) The system for modular construction of Claim 1 wherein at least one of said structural members includes a slot along the first widthwise side and the second widthwise side.

7.(currently amended) The system for modular construction of Claim 1 wherein at least one of said structural members includes a slot along the lengthwise side opposite the lengthwise side having said at least two slots, the first widthwise side and the second widthwise side.

8.(currently amended) The system for modular construction of Claim 1 wherein at least one of said structural members includes at least two slots along the first lengthwise side of said structural member and at least two slots along the second lengthwise side of said structural member whereby a first one of said at least two slots along the first lengthwise side defines a first lengthwise side first outside slot, a second one of said at least two slots along the first lengthwise side defines a first lengthwise side second outside slot, a first one of said at least two slots along the second lengthwise side defines a second lengthwise side first outside slot, and a second one of said at least two slots along the second lengthwise side defines a second lengthwise side second outside slot; wherein a said first lengthwise side first outside slot is located adjacent to the first widthwise side, a said first lengthwise side second outside slot is located adjacent to the second widthwise side, a the second lengthwise side first outside slot is located adjacent to the first widthwise side, and a the second lengthwise side second outside slot is located adjacent to the second widthwise side; and

wherein the distance between the slot axis of the first lengthwise side first outside slot and the first widthwise side is a first predetermined slot-to-side distance, the distance between the slot axis of the first lengthwise side second outside slot and the second widthwise side is a whole-number multiple of the first predetermined slot-to-side distance, the distance between the slot axis of the second lengthwise side first outside slot and the first widthwise side is a second predetermined slot-to-side distance, and the distance between the slot axis of the second lengthwise side second outside slot and the second widthwise side is a whole-number multiple of the second predetermined slot-to-side distance; and

wherein the distance between each of the slot axes of the at least two slots along the first lengthwise side is a whole-number multiple of the first predetermined slot-to-side distance, and the distance between each of the slot axes of the at least two slots along the second lengthwise side is a whole-number multiple of the second predetermined slot-to-side distance; and

wherein each of said plurality of structural members is adapted to be detachably connected slot-to-slot to each of the other of said plurality of structural members.

9.(original) The system for modular construction of Claim 8 wherein the first predetermined slot-to-side distance is equal to the second predetermined slot-to-side distance.

10.(original) The system for modular construction of Claim 8 wherein the distance between the slot axis of the first lengthwise side second outside slot and the second widthwise side is equal to the first predetermined slot-to-side distance, and the distance between the slot

axis of the second lengthwise side second outside slot and the second widthwise side is equal to the second predetermined slot-to-side distance.

- 11.(currently amended) The system for modular construction of Claim 1 wherein at least one of said structural members includes at least two slots along the first lengthwise side and at least two slots along the first widthwise side whereby a first one of said at least two slots along the first lengthwise side defines a first lengthwise side first outside slot, a second one of said at least two slots along the first lengthwise side defines a first lengthwise side second outside slot, a first one of said at least two slots along the first widthwise side defines a first widthwise side first outside slot, and a second one of said at least two slots along the first widthwise side defines a first widthwise side second outside slot, wherein a said first lengthwise side first outside slot is located adjacent to the first widthwise side, a said first lengthwise side second outside slot is located adjacent to the second widthwise side, a the first widthwise side first outside slot is located adjacent to the first lengthwise side, and a the first widthwise side second outside slot is located adjacent to the second lengthwise side; and wherein the distance between the slot axis of the first lengthwise side first outside slot and the first widthwise side is a first predetermined slot-to-side distance, the distance between the slot axis of the first lengthwise side second outside slot and the second widthwise side is a whole-number multiple of the first predetermined slot-to-side distance, the distance between the slot axis of the first widthwise side first outside slot and the first lengthwise side is a second predetermined slot-to-side distance, and the distance between the slot axis of the first widthwise side second outside slot and the

second lengthwise side is a whole-number multiple of the second predetermined slot-to-side distance; and

wherein the distance between each of the slot axes of the at least two slots along the first lengthwise side is a whole-number multiple of the first predetermined slot-to-side distance, and the distance between each of the slot axes of the at least two slots along the first widthwise side is a whole-number multiple of the second predetermined slot-to-side distance; and

wherein each of said plurality of structural members is adapted to be detachably connected slot-to-slot to each of the other of said plurality of structural members.

12.(original) The system for modular construction of Claim 11 wherein the first predetermined slot-to-side distance is equal to the second predetermined slot-to-side distance.

13.(original) The system for modular construction of Claim 11 wherein the distance between the slot axis of the first widthwise side second outside slot and the second lengthwise side is equal to the second predetermined slot-to-side distance.

14.(currently amended) The system for modular construction of Claim 1 wherein at least one of said structural members includes at least two slots along the first lengthwise side, at least two slots along the first widthwise side, and at least two slots along the second widthwise side whereby a first one of said at least two slots along the first lengthwise side defines a first lengthwise side first outside slot, a second one of said at least two slots along the first lengthwise side defines a first lengthwise side second outside slot, a first one of said

at least two slots along the first widthwise side defines a first widthwise side first outside slot, a second one of said at least two slots along the first widthwise side defines a first widthwise side second outside slot, a first one of said at least two slots along the second widthwise side defines a second widthwise side first outside slot, and a second one of said at least two slots along the second widthwise side defines a second widthwise side second outside slot;

wherein a the first lengthwise side first outside slot is located adjacent to the first widthwise side, -a the first lengthwise side second outside slot is located adjacent to the second widthwise side, -a the first widthwise side first outside slot is located adjacent to the first lengthwise side, a the first widthwise side second outside slot is located adjacent to the second lengthwise side, a the second widthwise side first outside slot is located adjacent to the first lengthwise side, and a the second widthwise side second outside slot is located adjacent to the second lengthwise side; and

wherein the distance between the slot axis of the first lengthwise side first outside slot and the first widthwise side is a first predetermined slot-to-side distance, the distance between the slot axis of the first lengthwise side second outside slot and the second widthwise side is a whole-number multiple of the first predetermined slot-to-side distance, the distance between the slot axis of the first widthwise side first outside slot and the first lengthwise side is a second predetermined slot-to-side distance, the distance between the slot axis of the first widthwise side second outside slot and the second lengthwise side is a whole-number multiple of the second predetermined slot-to-side distance, the distance between the slot axis of the second widthwise side first outside slot and the first lengthwise side is a third predetermined slot-to-side distance, and the

distance between the slot axis of the second widthwise side second outside slot and the second lengthwise side is a whole-number multiple of the third slot-to-side distance; and wherein the distance between each of the slot axes of the at least two slots along the first lengthwise side is a whole-number multiple of the first predetermined slot-to-side distance, the distance between each of the slot axes of the at least two slots along the first widthwise side is a whole-number multiple of the second predetermined slot-to-side distance, and the distance between each of the slot axes of the at least two slots along the second widthwise side is a whole-number multiple of the third predetermined slot-to-side distance; and wherein each of said plurality of structural members is adapted to be detachably connected slot-to-slot to each of the other of said plurality of structural members.

- 15.(original) The system for modular construction of Claim 14 wherein the second predetermined slot-to-side distance is equal to the third predetermined slot-to-side distance.
- 16.(original) The system for modular construction of Claim 14 wherein the first predetermined slot-to-side distance is equal to the second predetermined slot-to-side distance and the third predetermined slot-to-side distance.
- 17.(original) The system for modular construction of Claim 14 wherein the distance between the slot axis of the first lengthwise side second outside slot and the second widthwise side is equal to the first predetermined slot-to-side distance, the distance between the slot axis of

the first widthwise side second outside slot and the second lengthwise side is equal to the second predetermined slot-to-side distance, and the distance between the slot axis of the second widthwise side second outside slot and the second lengthwise side is equal to the third predetermined slot-to-side distance.

- 18.(currently amended) The system for modular construction of Claim 1 wherein at least one of said structural members includes at least two slots along the first lengthwise side, at least two slots along the second lengthwise side, at least two slots along the first widthwise side, and at least two slots along the second widthwise side whereby a first one of said at least two slots along the first lengthwise side defines a first lengthwise side first outside slot, a second one of said at least two slots along the first lengthwise side defines a first lengthwise side second outside slot, a first one of said at least two slots along the second lengthwise side defines a second lengthwise side first outside slot, a second one of said at least two slots along the second lengthwise side defines a second lengthwise side second outside slot, a first one of said at least two slots along the first widthwise side defines a first widthwise side first outside slot, a second one of said at least two slots along the first widthwise side defines a first widthwise side second outside slot, a first one of said at least two slots along the second widthwise side defines a second widthwise side first outside slot, and a second one of said at least two slots along the second widthwise side defines a second widthwise side second outside slot;
- wherein a the first lengthwise side first outside slot is located adjacent to the first widthwise side, a the first lengthwise side second outside slot is located adjacent to the second widthwise side, a the second lengthwise side first outside slot is located adjacent

to the first widthwise side, a the second lengthwise side second outside slot is located adjacent to the second widthwise side, a the first widthwise side first outside slot is located adjacent to the first lengthwise side, a the first widthwise side second outside slot is located adjacent to the second lengthwise side, a the second widthwise side first outside slot is located adjacent to the first lengthwise side, and a the second widthwise side second outside slot is located adjacent to the second lengthwise side; and wherein the distance between the slot axis of the first lengthwise side first outside slot and the first widthwise side is a first predetermined slot-to-side distance, the distance between the slot axis of the first lengthwise side second outside slot and the second widthwise side is a whole-number multiple of the first predetermined slot-to-side distance, the distance between the slot axis of the second lengthwise side first outside slot and the first widthwise side is a second predetermined slot-to-side distance, the distance between the slot axis of the second lengthwise side second outside slot and the second widthwise side is a whole-number multiple of the second predetermined slot-to-side distance, the distance between the slot axis of the first widthwise side first outside slot and the first lengthwise side is a third predetermined slot-to-side distance, the distance between the slot axis of the first widthwise side second outside slot and the second lengthwise side is a whole-number multiple of the third predetermined slot-to-side distance, the distance between the slot axis of the second widthwise side first outside slot and the first lengthwise side is a fourth predetermined slot-to-side distance, and the distance between the second widthwise side second outside slot and the second lengthwise side is a whole-number multiple of the fourth slot-to-side distance; and

wherein the distance between each of the slot axes of the at least two slots along the first lengthwise side is a whole-number multiple of the first predetermined slot-to-side distance, the distance between each of the slot axes of the at least two slots along the second lengthwise side is a whole-number multiple of the second predetermined slot-to-side distance, the distance between each of the slot axes of the at least two slots along the first widthwise side is a whole-number multiple of the third predetermined slot-to-side distance, and the distance between each of the slot axes of the at least two slots along the second widthwise side is a whole-number multiple of the fourth predetermined slot-to-side distance; and

wherein each of said plurality of structural members is adapted to be detachably connected slot-to-slot to each of the other of said plurality of structural members.

19.(original) The system for modular construction of Claim 18 wherein the first predetermined slot-to-side distance is equal to the second predetermined slot-to-side distance, the third predetermined slot-to-side distance and the fourth predetermined slot-to-side distance.

20.(original) The system for modular construction of Claim 18 wherein the distance between the slot axis of the first lengthwise side second outside slot and the second widthwise side is equal to the first predetermined slot-to-side distance, the distance between the slot axis of the second lengthwise side second outside member and the second widthwise side is equal to the second predetermined slot-to-side distance, the distance between the slot axis of the first widthwise side second outside slot and the second lengthwise side is equal to the third predetermined slot-to-side distance, and the distance between the slot axes of the

second widthwise side second outside slot and the second lengthwise side is equal to the fourth predetermined slot-to-side distance.

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☒ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.